

JQ Series Hammers equivalent to IR QL Series

MODEL	JQ20	JQ35	JQ40	JQ50	JQ60	JQ80	JQ100	JQ120	JQ130	JQ200
(SIZE)	(2")	(3.5")	(4")	(5")	(6")	(8")	(10")	(12")	(13")	(20")
SHANK TYPE	MACH20	DHD3.5	QL40	QL50	QL60	QL80	NUMA100	QL120	QL120	QL200
		XL3	DHD340	DHD350	DHD360	DHD380	SD10	DHD112	NUMA125	
		MACH303	SD4	SD5	SD6	SD8		SD12		
		COP34	MACH44	MACH50	XL6	MACH80		NUMA120		
					MACH60			NUMA125		
HOLE DIA.	(2-3/4"~3")	(3-3/8"~5")	(4-1/8"~5-1/8")	(5" ~ 6")	(5-7/8"~8-1/2")	(7-7/8"~10")	(10"~12-1/4")	(11-7/8~17-1/2")	(12.25"~17.5")	(17-1/2"~26")
HAMMER O.D.	(2.4")	(3.1")	(3.86")	(4.5")	(5.4")	(7.09")	(8.86")	(10.79")	(11.25")	(15.59")
CYLINDER BORE	(1.77")	(2.64")	(3.23")	(3.74")	(4.65")	(5.98")	(6.85")	(8.66")	(8.65")	(12.24")
LENGTH	(26.75")	(34")	(40.51")	(44.35")	(49.8")	(53.50")	(58.64")	(74.62")	(74.62")	(76.81")
WEIGHT	(28.7lb)	(44lb)	(82.9lb)	(126.4 lb)	(203.2 lb)	(366.7 lb)	(715 lb)	(1,364 lb)	(1,364 lb)	(3,392 lb)
TOP SUB	50mm DIN 405	2-3/8" API	2-3/8" API	3-1/2" API	3-1/2" API	4-1/2" API	6-5/8" API	6-5/8" API	6-5/8" API	8-5/8" API
CONNECTION	6TPI BOX	REG PIN	REG PIN	REG PIN	REG PIN	REG PIN	REG PIN	REG PIN	REG PIN	REG PIN
AIR CONSUMPTION, CFM(M³ /MIN)										
100PSI	70	140	150	180	.	.	400	750	750(21.2)	1,584(45.2)
150PSI	135	230	240	280	350	450	655	1,125	1,125(31.9)	2,470(70.5)
200PSI	205	330	340	400	565	530	945	1,675	1,675(47.4)	3,389(96.8)
250PSI	270	445		520	720	850	1,220	1,925	1,925(54.5)	4,341(124)
300PSI			540	660	875	1,080	1,475	2,475	2,475(70.1)	5,324(152.1)
350PSI			.	800	995	1,320	1,665	2,960	2,960(83.8)	6,340(181.1)
400PSI			.	.	1,130	1,500				